

EARTHMAX SR 41 - Specifiche tecniche



Description

EARTHMAX SR 41 è uno pneumatico radiale All Steel perfetto per dumper articolati, pale gommate e apripista. Grazie alla sua struttura interamente in acciaio e allo speciale profilo a blocco, EARTHMAX SR 41 offre un'eccellente resistenza contro le forature e una maggiore durata. Oltre a un'operatività prolungata senza tempi di fermo, lo pneumatico garantisce un comfort straordinario. EARTHMAX SR 41 è disponibile anche in SH-4**** per dumper a profilo basso (LPDT) utilizzati nelle operazioni di trasporto sotterraneo.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice • Dumper di basso profilo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25

Dimensions International Standard

Overall Width (mm)	761
Overall Diameter (mm)	1861
Static Loaded Radius (mm)	830
Rolling Circumference (mm)	5510
Rim Rec	25.00/3.5
Star Rating	****
TRA Code	SH4
Tread Depth	66

Load capacity (Kg)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 10:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..