

EARTHMAX SR 42 - Specifiche tecniche



Description

EARTHMAX SR 42 è uno pneumatico radiale OTR particolarmente progettato per i cosiddetti haul train nelle miniere e applicazioni pesanti per il trasporto di legname. Il caratteristico disegno del battistrada assicura eccellente trazione e stabilità laterale nonché prestazioni di frenatura e comportamento nelle curve ottimi su terreni accidentati o sulla ghiaia anche con neve e ghiaccio. Infatti, la mescola del battistrada, particolarmente resistente ai tagli e all'usura è molto idonea in condizioni climatiche estremamente fredde. EARTHMAX SR 42 presenta una carcassa All Steel che garantisce ottima durabilità e una lunga vita operativa.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Haul Train

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 25
LI/SS	171 B

Dimensions International Standard

TKPH	105
Overall Width (mm)	380
Overall Diameter (mm)	1412
Static Loaded Radius (mm)	652
Rolling Circumference (mm)	4231
Rim Rec	10.00/2.0
Rim Alt	--
Star Rating	***
TRA Code	E4
Tread Depth	38

Load capacity (Kg)

km/h / bar	7.00	8.00
50	5800	6150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..