

## EARTHMAX SR 43 - Specifiche tecniche



### Description

EARTHMAX SR 43 (L-4) è uno pneumatico radiale All Steel particolarmente progettato per pale gommate che operano in condizioni rocciose estreme, principalmente nelle miniere sotterranee. Lo pneumatico garantisce prestazioni eccellenti nelle operazioni di carico e di trasporto nelle miniere a cielo aperto, nelle cave e nei cantieri di demolizione. Il disegno unico del battistrada assicura trazione e stabilità superiori. Grazie alla struttura All Steel, EARTHMAX SR 43 (L-4) assicura eccellente durabilità e resistenza a lacerazioni e forature nonché un ciclo di vita più lungo.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	229 A2

## Dimensions International Standard

Overall Width (mm)	900
Overall Diameter (mm)	2076
Static Loaded Radius (mm)	957
Rolling Circumference (mm)	6412
Rim Rec	28.00/3.5
Star Rating	***
TRA Code	L4
Tread Depth	61

## Load capacity (Kg)

km/h / bar	6.75	7.00	7.25	7.50	7.75	8.00
10	29000	30000	30750	31500	32000	32500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 22:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..