

## EARTHMAX SR 43 - Scheda tecnica



### Description

EARTHMAX SR 43 (L-4) è uno pneumatico radiale All Steel particolarmente progettato per pale gommate che operano in condizioni rocciose estreme, principalmente nelle miniere sotterranee. Lo pneumatico garantisce prestazioni eccellenti nelle operazioni di carico e di trasporto nelle miniere a cielo aperto, nelle cave e nei cantieri di demolizione. Il disegno unico del battistrada assicura trazione e stabilità superiori. Grazie alla struttura All Steel, EARTHMAX SR 43 (L-4) assicura eccellente durabilità e resistenza a lacerazioni e forature nonché un ciclo di vita più lungo.

### UM

US Standard

### Construction



RADIAL

### Machinery

OTR: Pala caricatrice

| SIZE                        | Version                | USACode  | TRA Code | Star R   | LI/SS  | RIM REC   | RIM ALT              | OW   | OD   | SLR  | RC    | Type | Tread Depth |
|-----------------------------|------------------------|----------|----------|----------|--------|-----------|----------------------|------|------|------|-------|------|-------------|
| 29.5 R 25                   | CUT RESISTANT COMPOUND | 94063291 | L4       | **       | 216 A2 | 25.00/3.5 |                      | 30.9 | 73.8 | 33.3 | 222.2 | TL   | 77          |
| 29.5 R 25                   | CUT RESISTANT COMPOUND | 94063390 | L4       | ***      | 221 A2 | 25.00/3.5 |                      | 30.9 | 73.8 | 33.3 | 222.2 | TL   | 77          |
| 29.5 R 29                   | CUT RESISTANT COMPOUND | 94051021 | L4       | ***      | 223 A2 | 25.00/3.5 | 24.00/3.5, 26.00/3.5 | 30.2 | 78.9 | 35.6 | 237.4 | TL   | 78          |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND | 94071098 | L4       | ***      | 228 A2 | 27.00/3.5 | 27.00/3.0; 28.00/3.5 | 33.5 | 73.9 | 33.2 | 224.5 | TL   | 77          |
| 35/65 R 33                  | CUT RESISTANT COMPOUND | 94068869 | L4       | ***      | 229 A2 | 28.00/3.5 |                      | 35.4 | 81.7 | 37.7 | 252.4 | TL   | 77          |
| 35/65 R 33                  | CUT RESISTANT COMPOUND | 94067312 | L4       | **       | 224 A2 | 28.00/3.5 |                      | 35.4 | 81.7 | 37.7 | 252.4 | TL   | 77          |
| 35/65 R 33                  | CUT RESISTANT COMPOUND | 94069903 | E4/L4    | ****/*** |        | 28.00/3.5 |                      | 35.4 | 81.7 | 37.7 | 252.4 | TL   | 77          |
| 35/65 R 33                  | CUT RESISTANT COMPOUND | 94069910 | SH4      | ****     |        | 28.00/3.5 |                      | 35.4 | 81.7 | 37.7 | 252.4 | TL   | 77          |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 07:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..