

EARTHMAX SR 44 - Specifiche tecniche



Description

EARTHMAX SR 44 è uno pneumatico radiale **All Steel** idoneo per una serie di applicazioni incluse operazioni in miniera, di trasporto e forestiere. Il robusto disegno del battistrada E-4 assicura eccellente trazione e comfort per l'operatore. EARTHMAX SR 44 (E-4) è in grado di ottimizzare la produttività, qualunque sia la vostra operazione.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Carro con cassone ribaltabile

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	146/143 G

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	268
Overall Diameter (mm)	1075
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3200
Rim Rec	7.50
Rim Alt	7.0 ; 7.50VM ; 8.0
ECE	E11-54R-0015908
Tread Depth	25

Load capacity (Kg)

km/h / bar	8.3
90	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..