

EARTHMAX SR 46 - Specifiche tecniche



Description

Earthmax SR 46 per dumper rigidi è la risposta innovativa agli ambienti rocciosi, abrasivi ed ostili delle miniere. Questo pneumatico è stato particolarmente progettato per il trasporto di carichi pesanti ed offre una resistenza eccezionale a tagli e lacerazioni nonché un ciclo di vita più lungo del prodotto. La carcassa e le cinture All Steel assicurano una protezione straordinaria contro colpi, sollecitazioni e forature per massimizzare le ore operative e incrementare la produttività. Earthmax SR 46 è caratterizzato da uno speciale disegno del battistrada dotato di ramponi a blocchi con scanalatura lungo la circonferenza. Ne conseguono ottime prestazioni in curva con danno minimo alla parte esterna del battistrada.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	33.00 R 51
LI/SS	235 B

Dimensions US Standard

Usa code	94067350
TMPH	548
Overall Width (inch)	35.6
Overall Diameter (inch)	120.1
Static Loaded Radius (inch)	55.2
Rolling Circumference (inch)	369.2
Rim Rec	24.00/5.0
Star Rating	**
TRA Code	E4
Tread Depth	110

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	66000	68000	71500	74000	76000	78500	80500	82500	85500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/05/2025 13:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..