

EARTHMAX SR LOADER - Specifiche tecniche



Description

EARTHMAX SR LOADER è uno pneumatico OTR particolarmente progettato per le operazioni di carico e spianamento, nonché per applicazioni di trasporto con dumper articolati. La sua carcassa All Steel rinforzata con cinture in acciaio multistrato e l'esclusiva mescola del battistrada offrono eccezionale resistenza a strappi e forature che si traducono in una vita prolungata dello pneumatico. EARTHMAX SR LOADER è dotato di un esclusivo disegno del battistrada che assicura ottime proprietà autopulenti e trazione eccellente su svariati tipi di terreno.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

Dimensions US Standard

Usa code	94064250
TMPH	116
Overall Width (inch)	20.9
Overall Diameter (inch)	58.1
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	172.6
Rim Rec	17.00/2.0
Star Rating	**/*
TRA Code	E3/L3
Tread Depth	37

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	12800	13600	14300	14800	15200	16100
5	17600	18200	19300	19800	20900	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 23:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..