



EM 934 - Scheda tecnica



Description

EM 934 è stato particolarmente sviluppato per escavatori nelle applicazioni per la costruzione delle strade, offrendo eccellente trazione laterale nonché straordinarie qualità di auto-pulitura. La mescola unica del battistrada è particolarmente resistente a tagli e lacerazioni mentre la carcassa robusta assicura una lunga vita operativa.

UM

International Standard

Construction

❖ BIAS

Machinery

Industriale: Escavatore

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 - 20	SPECIAL	E2	146 B	16	7.5	7.0 ; 8.0	280	1060	500	3208	TT
10.00 - 20	STANDARD	E2	146 B	16	7.5	7.0 ; 8.0	280	1060	500	3208	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 23:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..