

EM 936 LOADER SPECIAL - Specifiche tecniche



Description

EM 936 LOADER SPECIAL è stato specialmente progettato per sollevatori telescopici/telehandler nelle applicazioni di carico. Assicura un elevato comfort nella movimentazione, fornendo eccellente trazione anche in condizioni di servizio pesante.

UM

US Standard

Construction

✚ BIAS

Machinery

Industriale: Pala caricatrice • Sollevatore telescopico

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20 (405/70 - 20)
LI/SS	149 B

Dimensions US Standard

Usa code	94028771
Ply Rating	14
Overall Width (inch)	15.9
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	129.7
Rim Rec	13 SDC
Rim Alt	13
TRA Code	E2

Load capacity (lbs)

mph / psi	51
30	7150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 12:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..