

EM 937 (E3) - Specifiche tecniche



Description

EM 937 (E-3) è stato particolarmente progettato per dumper rigidi nelle applicazioni di miniera a cielo aperto. Lo pneumatico offre eccellente durabilità insieme ad elevata resistenza a tagli e strappi. EM 937 (E-3) è particolarmente idoneo per operazioni di servizio pesante.

UM

US Standard

Construction

✚ BIAS

Machinery

OTR: Dumper rigido

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

Dimensions US Standard

Usa code	94015443
Ply Rating	28
Overall Width (inch)	14.8
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	161.6
Rim Rec	10.00/1.5
TRA Code	E3/L3
Tread Depth	33

Load capacity (lbs)

mph / psi	94	134
30	12300	-
5	-	22000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 06:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..