

EM 939 - Specifiche tecniche



Description

EM 939 è stato particolarmente sviluppato per escavatori nelle applicazioni di costruzione stradale. Il battistrada più profondo e il maggiore numero di tasselli garantiscono una vita prolungata dello pneumatico. Il particolare disegno dei ramponi offre eccellente trazione nelle operazioni su e fuori strada. Lo pneumatico si distingue per l'ottima trazione laterale nonché straordinarie proprietà di autopulitura. La miscela unica del battistrada offre eccellente resistenza a tagli e lacerazioni, mentre la carcassa robusta assicura una lunga vita operativa.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Escavatore

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	260
Overall Diameter (mm)	1025
Rim Rec	7.0
Rim Alt	6.5 ; 7.5

Load capacity (Kg)

km/h / bar	8.50
50	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 01:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..