

FARM 2000 - Specifiche tecniche



Description

Lo pneumatico FARM 2000 è idoneo per trattori nelle applicazioni per la lavorazione del suolo. È stato realizzato con una mescola speciale resistente a tagli e lacerazioni che assicura una durabilità migliore. Grazie alla carcassa robusta, FARM 2000 offre elevata capacità di carico nonché trazione e proprietà di autopulitura eccellenti.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	130 A8

Dimensions US Standard

Usa code	94031764
Ply Rating	12
Section Width (inch)	15.2
Overall Diameter (inch)	54.1
Static Loaded Radius (inch)	25
Rolling Circumference (inch)	165.1
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E11-106R-005966
TRA Code	R1

Load capacity (lbs)

mph / psi	33
25	4180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 23:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..