

## FARM SPECIAL - Specifiche tecniche



### Description

FARM SPECIAL è uno pneumatico per trattori idoneo per la lavorazione del terreno. La carcassa robusta garantisce un elevato livello di resistenza alle forature e una vita operativa più lunga, mentre le spalle arrotondate evitano danni al suolo proteggendo le colture preziose. FARM SPECIAL si distingue per il suo unico disegno del battistrada con elementi mud breaker che spezzano il fango ottimizzando le proprietà di autopulitura. Inoltre, la doppia angolazione dei tasselli assicura ottima trazione con minore slittamento.

### UM

International Standard

### Construction

BIAS

### Machinery

Agricoltura: Trattore

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 13.6 - 24 |
| LI/SS     | 123 A6    |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 8               |
| Section Width (mm)         | 350             |
| Overall Diameter (mm)      | 1205            |
| Static Loaded Radius (mm)  | 554             |
| Rolling Circumference (mm) | 3635            |
| Rim Rec                    | W 12            |
| Rim Alt                    | W 11            |
| ECE                        | E11-106R-005530 |
| TRA Code                   | R1              |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.00 |
| 30         | 1550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 08:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..