

FL 252 - Scheda tecnica



Description

FL 252 è uno pneumatico idoneo per applicazioni di raccolta del fieno con ranghinatori/voltafieno nonché operazioni logistiche con carrelli elevatori. Lo pneumatico garantisce un'eccellente durabilità, mentre lo specifico disegno del battistrada assicura massima stabilità durante le operazioni di sollevamento.

UM

International Standard

Construction

BIAS

Machinery

Agricoltura: Ranghinatore

Industriale: Carrello elevatore

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
5.00 - 8	STANDARD	8	3.00 D	3.25 I	138	480	TT
5.00 - 8	STANDARD	10	3.00 D	3.25 I	138	480	TT
6.00 - 9	STANDARD	10	4.00 E		170	550	TT
6.50 - 10	STANDARD	10	5.00 F	5.50 F	185	605	TT
7.00 - 12	STANDARD	14	5.00 S		192	683	TT
8.15 - 15 (28 X 9 - 15)	STANDARD	14	7.00	7 BD	220	720	TT
8.25 - 15	STANDARD	14	6.50	7.0	240	855	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..