

FL 630 SUPER - Specifiche tecniche



Description

FL 630 SUPER è uno pneumatico Flotation idoneo per le applicazioni su campo e su strada con l'impiego di rimorchi, autobotti e spargitori. La sua struttura resistente offre un'eccellente trazione, durabilità e presa perfetta anche in curva e durante le manovre. Il particolare disegno del battistrada è sinonimo di elevata capacità di galleggiamento che riduce la compattazione del suolo oltre a proprietà di autopulitura avanzate. FL 630 SUPER può raggiungere velocità fino a 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Spargitore • Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	165 D

Dimensions US Standard

Usa code	94059539
Section Width (inch)	21.4
Overall Diameter (inch)	49
Static Loaded Radius (inch)	21.6
Rolling Circumference (inch)	149
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E11-106R-006945

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73
45	3430	3850	4780	5430	6280	7120	7780	8530	9370	10470
40	3730	4190	5200	5920	6830	7750	8470	9280	10200	11350
30	4520	5070	6300	7160	8280	9390	10250	11240	12350	13750
25	5070	5690	7080	8050	9290	10550	11520	12620	13870	15440
15	5890	6610	8220	9350	10800	12260	13380	14670	16110	17940
5	6700	7530	9370	10650	12300	13950	15230	16710	18350	20440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..