

## FL 630 SUPER - Specifiche tecniche



### Description

FL 630 SUPER è uno pneumatico Flotation idoneo per le applicazioni su campo e su strada con l'impiego di rimorchi, autobotti e spargitori. La sua struttura resistente offre un'eccellente trazione, durabilità e presa perfetta anche in curva e durante le manovre. Il particolare disegno del battistrada è sinonimo di elevata capacità di galleggiamento che riduce la compattazione del suolo oltre a proprietà di autopulitura avanzate. FL 630 SUPER può raggiungere velocità fino a 70 km/h.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Spargitore • Autobotte • Rimorchio

|           |               |
|-----------|---------------|
| Version   | HD            |
| Type      | TL            |
| Tyre Size | 600/55 R 26.5 |
| LI/SS     | 177 D         |

# Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94048946        |
| Section Width (inch)         | 24.1            |
| Overall Diameter (inch)      | 52.5            |
| Static Loaded Radius (inch)  | 23.8            |
| Rolling Circumference (inch) | 161.6           |
| Rim Rec                      | AG 20.00        |
| ECE                          | E11-106R-003005 |

## Load capacity (lbs)

| mph / psi | 12   | 15   | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    | 73    | 87    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | 4020 | 4990 | 5960  | 7240  | 8380  | 9660  | 10950 | 11750 | 13040 | 14330 | 15130 | 16090 |
| 30        | 4870 | 6040 | 7210  | 8770  | 10130 | 11690 | 13250 | 14220 | 15780 | 17340 | 18310 | 19480 |
| 25        | 5480 | 6790 | 8100  | 9850  | 11390 | 13140 | 14890 | 15980 | 17740 | 19490 | 20580 | 21890 |
| 20        | 6080 | 7540 | 8990  | 10950 | 12640 | 14580 | 16530 | 17750 | 19700 | 21640 | 22850 | 24300 |
| 15        | 6360 | 7890 | 9410  | 11450 | 12320 | 15270 | 17290 | 18570 | 20600 | 22640 | 23910 | 25430 |
| 5         | 7240 | 8980 | 10720 | 13040 | 15070 | 17380 | 19710 | 21150 | 23470 | 25780 | 27240 | 28970 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..