

FL 633 PERFORMA - Specifiche tecniche



Description

Il nuovo pneumatico radiale All Steel FL 633 PERFORMA combina perfettamente le esigenze di svariate applicazioni agricole con la crescente domanda di logistica in agricoltura. Progettato particolarmente per i camion agricoli, FL 633 PERFORMA è la soluzione innovativa che migliora le prestazioni di trattore e camion al fine di soddisfare le esigenze specifiche dell'agricoltura moderna. Grazie alla carcassa molto robusta, a capacità di carico e durabilità elevate, FL 633 PERFORMA segna il "next level" degli pneumatici Flotation idonei per molteplici attività sul campo e persino spostamenti su autostrada fino a 100 km/h.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Camion agricolo

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	164 J

Dimensions International Standard

Overall Width (mm)	590
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	534
Rolling Circumference (mm)	3559
Rim Rec	AG 20.00
ECE	E11-54R-0017858

Load capacity (Kg)

km/h / bar	6.50
100	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..