



## FL 633 PERFORMA - Scheda tecnica



### Description

Il nuovo pneumatico radiale All Steel FL 633 PERFORMA combina perfettamente le esigenze di svariate applicazioni agricole con la crescente domanda di logistica in agricoltura. Progettato particolarmente per i camion agricoli, FL 633 PERFORMA è la soluzione innovativa che migliora le prestazioni di trattore e camion al fine di soddisfare le esigenze specifiche dell'agricoltura moderna. Grazie alla carcassa molto robusta, a capacità di carico e durabilità elevate, FL 633 PERFORMA segna il "next level" degli pneumatici Flotation idonei per molteplici attività sul campo e persino spostamenti su autostrada fino a 100 km/h.

### UM

International Standard

### Construction



### Machinery

Agricoltura: Camion agricolo

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
<b>600/50 R 22.5</b>	STANDARD	164 J	AG 20.00		590	1170	534	3559	TL	E11-54R-0017858

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..