

FL 635 - Specifiche tecniche



Description

FL 635 è uno pneumatico radiale Flotation idoneo per l'impiego sia su strada sia su campo. Il particolare disegno a blocchi del battistrada è stato sviluppato per applicazioni di presse per balle di fieno. Grazie all'impronta che fornisce l'ottima distribuzione della pressione sul terreno, lo pneumatico FL 635 riduce nettamente la compattazione del suolo preservando il valore delle colture. Lo pneumatico è dotato di ottime proprietà di autopulitura, durabilità e trazione, insieme a eccellenti caratteristiche di velocità.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Pressa per balle di fieno

Version	STANDARD
Type	TL
Tyre Size	620/40 R 22.5
LI/SS	154 D

Dimensions US Standard

Usa code	94048038
Section Width (inch)	24.6
Overall Diameter (inch)	42
Static Loaded Radius (inch)	18.5
Rolling Circumference (inch)	127.9
Rim Rec	AG 20.00
ECE	E4-106R-002399

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2410	2760	3100	3850	4380	5050	5730	6250	6860	7530
40	2650	3020	3390	4220	4790	5540	6280	6870	7530	8270
30	3210	3660	4110	5110	5810	6710	7620	8310	9120	10010
25	3600	4110	4620	5740	6530	7540	8550	9340	10240	11240
15	4190	4770	5360	6670	7580	8750	9930	10850	11890	13060
5	4760	5430	6110	7590	8630	9980	11310	12360	13550	14880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..