

## FL 635 - Specifiche tecniche



### Description

FL 635 è uno pneumatico radiale Flotation idoneo per l'impiego sia su strada sia su campo. Il particolare disegno a blocchi del battistrada è stato sviluppato per applicazioni di presse per balle di fieno. Grazie all'impronta che fornisce l'ottima distribuzione della pressione sul terreno, lo pneumatico FL 635 riduce nettamente la compattazione del suolo preservando il valore delle colture. Lo pneumatico è dotato di ottime proprietà di autopulitura, durabilità e trazione, insieme a eccellenti caratteristiche di velocità.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agricoltura: Pressa per balle di fieno

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 750/45 R 22.5 |
| LI/SS     | 168 D         |

# Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 754            |
| Overall Diameter (mm)      | 1247           |
| Static Loaded Radius (mm)  | 555            |
| Rolling Circumference (mm) | 3810           |
| SRI (mm)                   | 600            |
| Rim Rec                    | AG 24.00       |
| ECE                        | E4-106R-002653 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0   |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 70         | 1635 | 1865 | 2095 | 2605 | 2960 | 3420 | 3880 | 4235 | 4645 | 5100  |
| 65         | 1795 | 2050 | 2300 | 2860 | 3250 | 3755 | 4260 | 4650 | 5100 | 5600  |
| 50         | 2170 | 2475 | 2780 | 3460 | 3935 | 4545 | 5155 | 5630 | 6170 | 6780  |
| 40         | 2440 | 2785 | 3125 | 3890 | 4420 | 5110 | 5795 | 6325 | 6935 | 7620  |
| 30         | 2710 | 3090 | 3470 | 4315 | 4910 | 5670 | 6430 | 7025 | 7700 | 8460  |
| 25         | 2835 | 3235 | 3630 | 4515 | 5135 | 5930 | 6730 | 7350 | 8055 | 8850  |
| 10         | 3230 | 3685 | 4135 | 5145 | 5850 | 6755 | 7665 | 8370 | 9175 | 10080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..