

## FL 637 - Specifiche tecniche



### Description

FL 637 è uno pneumatico radiale Flotation idoneo per spargitori, rimorchi e autobotti. La struttura del battistrada rinforzata garantisce durabilità superiore e maggiore capacità di carico. Oltre alle eccellenti proprietà di galleggiamento, che si traducono in una ridotta compattazione del suolo, questo pneumatico vanta delle straordinarie proprietà di autopulitura. Il disegno direzionale del battistrada assicura una trazione eccellente consentendo velocità fino a 70 km/h

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Spargitore • Autobotte • Rimorchio

|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TL          |
| Tyre Size | 520/50 R 17 |
| LI/SS     | 151D/148E   |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 516             |
| Overall Diameter (mm)      | 952             |
| Static Loaded Radius (mm)  | 414             |
| Rolling Circumference (mm) | 2930            |
| SRI (mm)                   | 450             |
| Rim Rec                    | 16.00           |
| ECE                        | E11-106R-004070 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 5.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 915  | 1170 | 1420 | 1610 | 1860 | 2115 | 2335 | 2555 | 2805 | 3150 |
| 65         | 1005 | 1280 | 1555 | 1760 | 2040 | 2315 | 2555 | 2795 | 3075 | 3450 |
| 50         | 1215 | 1545 | 1880 | 2130 | 2465 | 2800 | 3090 | 3385 | 3720 | 4175 |
| 40         | 1365 | 1740 | 2115 | 2395 | 2775 | 3150 | 3475 | 3805 | 4180 | 4695 |
| 30         | 1515 | 1930 | 2345 | 2660 | 3075 | 3495 | 3860 | 4225 | 4640 | 5210 |
| 25         | 1585 | 2020 | 2455 | 2785 | 3220 | 3655 | 4040 | 4420 | 4855 | 5455 |
| 10         | 1805 | 2300 | 2795 | 3170 | 3665 | 4165 | 4600 | 5035 | 5530 | 6210 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..