

## FL 639 - Specifiche tecniche



### Description

FL 639 è uno pneumatico Flotation per un impiego principalmente sul campo particolarmente idoneo per applicazioni con spargitori. L'impronta larga garantisce una ridotta compattazione del suolo che favorisce una maggiore produttività delle colture. Il battistrada rinforzato e la protezione del fianco contribuiscono ad un ciclo di vita più lungo. FL 639 assicura inoltre una trazione straordinaria nonché ottime proprietà di autopulitura.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Spargitore

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 600/50 R 22.5 |
| LI/SS     | 159 D/170 A8  |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94028153       |
| Section Width (inch)         | 24.1           |
| Overall Diameter (inch)      | 46.1           |
| Static Loaded Radius (inch)  | 20.9           |
| Rolling Circumference (inch) | 139.4          |
| Rim Rec                      | AG 20.00       |
| ECE                          | E4-106R-000802 |

## Load capacity (lbs)

| mph / psi | 12   | 15   | 17   | 23   | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45        | 2820 | 3260 | 3690 | 4450 | 5190  | 5910  | 6660  | 7340  | 8090  | 8780  |
| 40        | 3090 | 3570 | 4060 | 4890 | 5700  | 6500  | 7300  | 8070  | 8870  | 9640  |
| 30        | 3740 | 4320 | 4910 | 5950 | 6890  | 7880  | 8820  | 9740  | 10750 | 11670 |
| 25        | 4230 | 4890 | 5560 | 6700 | 7800  | 8930  | 10040 | 11070 | 12170 | 13230 |
| 15        | 4880 | 5640 | 6400 | 7740 | 8990  | 10310 | 11490 | 12790 | 14030 | 15240 |
| 5         | 5560 | 6430 | 7300 | 8820 | 10250 | 11740 | 13090 | 14550 | 15970 | 17360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..