

FL 639 - Specifiche tecniche



Description

FL 639 è uno pneumatico Flotation per un impiego principalmente sul campo particolarmente idoneo per applicazioni con spargitori. L'impronta larga garantisce una ridotta compattazione del suolo che favorisce una maggiore produttività delle colture. Il battistrada rinforzato e la protezione del fianco contribuiscono ad un ciclo di vita più lungo. FL 639 assicura inoltre una trazione straordinaria nonché ottime proprietà di autopulitura.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Spargitore

Version	STANDARD
Type	TL
Tyre Size	850/40 R 26.5
LI/SS	173 D / 184 A8

Dimensions International Standard

Section Width (mm)	860
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	599
Rolling Circumference (mm)	4122
SRI (mm)	650
Rim Rec	AG 28.00
ECE	E11-106R-006228

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1895	2430	3020	3435	3965	4500	4910	5385	5915
65	2080	2665	3315	3770	4355	4940	5395	5915	6500
50	2520	3225	4015	4565	5270	5980	6530	7160	7865
40	2880	3690	4590	5220	6030	6840	7470	8190	9000
30	3145	4025	5010	5695	6580	7460	8150	8935	9815
25	3290	4215	5240	5960	6885	7810	8525	9350	10270
10	3745	4800	5970	6790	7840	8895	9715	10650	11700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 17:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..