

## FLOTATION 558 - Scheda tecnica



### Description

FLOTATION 558 è uno pneumatico Flotation a tele incrociate idoneo per mietitrici e presse per balle di fieno, autocisterne e rimorchi sia su strada che fuori strada. È particolarmente raccomandato in tutti i casi in cui la trazione è essenziale per una buona lavorazione del terreno oltre all'elevata capacità di carico.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •  
Autobotte • Rimorchio

| SIZE          | Version          | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC  | RIM ALT                  | SW  | OD   | SLR | RC   | Type | ECE             |
|---------------|------------------|-------------------|--------------------|----|----------|--------------------------|-----|------|-----|------|------|-----------------|
| 400/55 - 22.5 | ARAMID BELTED HD | 140 A8/136 B      | 152 A8/148 B       | 16 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 405 | 1020 | 445 | 3084 | TL   | E11-106R-005350 |
| 400/55 - 22.5 | STANDARD         | 144 A8/140 B      | 156 A8/152 B       | 20 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 405 | 1020 | 445 | 3084 | TL   | E11-106R-005351 |
| 400/55 - 22.5 | STANDARD         | 138 A8/134 B      | 150 A8/146 B       | 14 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 405 | 1020 | 445 | 3084 | TL   | E4-106R-002261  |
| 400/55 - 22.5 | STANDARD         | 140 A8/136 B      | 152 A8/148 B       | 16 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 405 | 1020 | 445 | 3084 | TL   | E4-106R-002262  |
| 500/45 - 22.5 | ARAMID BELTED HD | 142 A8/138 B      | 154 A8/150 B       | 16 | AG 16.00 |                          | 500 | 1045 | 471 | 3167 | TL   | E11-106R-005352 |
| 500/45 - 22.5 | STANDARD         | 136 A8/132 B      | 148 A8/144 B       | 12 | AG 16.00 |                          | 500 | 1045 | 471 | 3167 | TL   | E4-106R-002307  |
| 500/45 - 22.5 | STANDARD         | 142 A8/138 B      | 154 A8/150 B       | 16 | AG 16.00 |                          | 500 | 1045 | 471 | 3167 | TL   | E4-106R-002315  |
| 500/45 - 22.5 | STANDARD         | 146 A8/142 B      | 158 A8/154 B       | 20 | AG 16.00 |                          | 500 | 1045 | 471 | 3167 | TL   | E11-106R-005353 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..