

FLOTATION 648 - Specifiche tecniche



Description

FLOTATION 648 è particolarmente idoneo per trasporti su campo e su strada nonché applicazioni di spargitori. Alcune misure sono idonee per mietitrici/presse per balle di fieno. Il particolare disegno del battistrada consente il trasporto di carichi molto pesanti a pressioni basse, garantendo di conseguenza una compattazione ridotta del suolo e proteggendo nel contempo le colture da danni.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Spargitore

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS DRIVE WHEEL	156 A8/152 B
LI/SS FREE ROLLING	169 A8/165 B

Dimensions International Standard

Ply Rating	18
Section Width (mm)	550
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3725
Rim Rec	AG 16.00
ECE	E4-106R-001565

Load capacity (Kg)

km/h / bar	3.00	3.10	3.20
10 FR	7820	7975	8120
20 FR	7035	7175	7310
30 FR	6255	6380	6495
40 FR	5585	5695	5800
50 FR	5025	5125	5150
10 DW	5390	5495	5600
20 DW	4850	4945	5040
30 DW	4310	4395	4480
40 DW	3850	3925	4000
50 DW	3465	3535	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..