

FLOTATION 648 - Specifiche tecniche



Description

FLOTATION 648 è particolarmente idoneo per trasporti su campo e su strada nonché applicazioni di spargitori. Alcune misure sono idonee per mietitrici/presse per balle di fieno. Il particolare disegno del battistrada consente il trasporto di carichi molto pesanti a pressioni basse, garantendo di conseguenza una compattazione ridotta del suolo e proteggendo nel contempo le colture da danni.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Spargitore

Version	STANDARD
Type	TL
Tyre Size	600/50 - 22.5
LI/SS DRIVE WHEEL	147 A8/144 B
LI/SS FREE ROLLING	159 A8/156 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	611
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	510
Rolling Circumference (mm)	3501
Rim Rec	AG 20.00
ECE	E4-106R-002312

Load capacity (Kg)

km/h / bar	1.50	1.70	2.00
10 FR	5175	5570	6125
20 FR	4655	5015	5515
30 FR	4140	4460	4900
40 FR	3695	3980	4375
50 FR	3325	3580	4000
10 DW	3640	3915	4305
20 DW	3275	3520	3875
30 DW	2910	3130	3445
40 DW	2600	2795	3075
50 DW	2340	2515	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..