

FLOTATION 648 - Specifiche tecniche



Description

FLOTATION 648 è particolarmente idoneo per trasporti su campo e su strada nonché applicazioni di spargitori. Alcune misure sono idonee per mietitrici/presse per balle di fieno. Il particolare disegno del battistrada consente il trasporto di carichi molto pesanti a pressioni basse, garantendo di conseguenza una compattazione ridotta del suolo e proteggendo nel contempo le colture da danni.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Spargitore

Version	STANDARD
Type	TL
Tyre Size	600/55 - 26.5
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B

Dimensions US Standard

Usa code	94006434
Ply Rating	12
Section Width (inch)	24.1
Overall Diameter (inch)	53.3
Static Loaded Radius (inch)	22.9
Rolling Circumference (inch)	158.1
Rim Rec	AG 20.00
ECE	E4-106R-002277

Load capacity (lbs)

mph / psi	22	26	29
5 FR	13430	14940	15890
10 FR	12080	13450	14310
20 FR	10740	11950	12720
25 FR	9590	10670	11350
30 FR	8630	9600	10200
5 DW	9520	10580	11260
10 DW	8560	9520	10140
20 DW	7620	8470	9020
25 DW	6800	7560	8050
30 DW	6120	6800	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..