

FLOTATION 648 - Specifiche tecniche



Description

FLOTATION 648 è particolarmente idoneo per trasporti su campo e su strada nonché applicazioni di spargitori. Alcune misure sono idonee per mietitrici/presse per balle di fieno. Il particolare disegno del battistrada consente il trasporto di carichi molto pesanti a pressioni basse, garantendo di conseguenza una compattazione ridotta del suolo e proteggendo nel contempo le colture da danni.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Spargitore

Version	HD
Type	TL
Tyre Size	650/65 - 30.5
LI/SS DRIVE WHEEL	169 A8/165 B
LI/SS FREE ROLLING	181 A8/178 B

Dimensions US Standard

Usa code	94030279
Ply Rating	18
Section Width (inch)	26.4
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 20.00
ECE	E11-106R-004563

Load capacity (lbs)

mph / psi	33	35	36
5 FR	24240	24860	25460
10 FR	21810	22380	22920
20 FR	19400	19880	20370
25 FR	17320	17760	18190
30 FR	15590	15980	16530
5 DW	17050	17480	17900
10 DW	15340	15740	16110
20 DW	13650	13990	14320
25 DW	12180	12490	12790
30 DW	10970	11240	11350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..