

## FLOTATION 648 - Specifiche tecniche



### Description

FLOTATION 648 è particolarmente idoneo per trasporti su campo e su strada nonché applicazioni di spargitori. Alcune misure sono idonee per mietitrici/presse per balle di fieno. Il particolare disegno del battistrada consente il trasporto di carichi molto pesanti a pressioni basse, garantendo di conseguenza una compattazione ridotta del suolo e proteggendo nel contempo le colture da danni.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Spargitore

|                    |               |
|--------------------|---------------|
| Version            | STANDARD      |
| Type               | TL            |
| Tyre Size          | 700/50 - 26.5 |
| LI/SS DRIVE WHEEL  | 162 A8/158 B  |
| LI/SS FREE ROLLING | 174 A8/170 B  |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 16             |
| Section Width (mm)         | 700            |
| Overall Diameter (mm)      | 1373           |
| Static Loaded Radius (mm)  | 621            |
| Rolling Circumference (mm) | 4099           |
| Rim Rec                    | 24.00          |
| ECE                        | E4-106R-002279 |

## Load capacity (Kg)

| km/h / bar | 2.00 | 2.20 | 2.40 |
|------------|------|------|------|
| 10 FR      | 8430 | 8910 | 9380 |
| 20 FR      | 7585 | 8020 | 8440 |
| 30 FR      | 6740 | 7130 | 7505 |
| 40 FR      | 6020 | 6365 | 6700 |
| 50 FR      | 5420 | 5730 | 6000 |
| 10 DW      | 5980 | 6320 | 6650 |
| 20 DW      | 5380 | 5690 | 5985 |
| 30 DW      | 4780 | 5055 | 5320 |
| 40 DW      | 4270 | 4515 | 4750 |
| 50 DW      | 3845 | 4065 | 4250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..