

FLOTATION 648 - Specifiche tecniche



Description

FLOTATION 648 è particolarmente idoneo per trasporti su campo e su strada nonché applicazioni di spargitori. Alcune misure sono idonee per mietitrici/presse per balle di fieno. Il particolare disegno del battistrada consente il trasporto di carichi molto pesanti a pressioni basse, garantendo di conseguenza una compattazione ridotta del suolo e proteggendo nel contempo le colture da danni.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Spargitore

Version	STANDARD
Type	TL
Tyre Size	750/60 - 30.5
LI/SS DRIVE WHEEL	164 A8/160 B
LI/SS FREE ROLLING	176 A8/172 B

Dimensions US Standard

Usa code	94006533
Ply Rating	12
Section Width (inch)	29.7
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 24.00
ECE	E11-106R-003410

Load capacity (lbs)

mph / psi	22	23	25
5 FR	20370	21150	21910
10 FR	18330	19040	19720
20 FR	16290	16930	17530
25 FR	14550	15110	15650
30 FR	13090	13600	13890
5 DW	14340	14890	15430
10 DW	12910	13400	13890
20 DW	11460	11920	12350
25 DW	10240	10640	11020
30 DW	9210	9580	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..