

FLOTATION RIB IMPLEMENT - Specifiche tecniche



Description

FLOTATION RIB IMPLEMENT è uno pneumatico con scanalature specifiche per rimorchi, attrezzi agricoli e presse per balle di fieno nelle applicazioni di trasporto e di raccolta del fieno. Lo pneumatico si distingue per l'elevata capacità di carico e un lungo ciclo di vita.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	31 X 13.50 - 15
LI/SS	124 B

Dimensions US Standard

Usa code	94040469
Ply Rating	12
Section Width (inch)	14.2
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	94.4
Rim Rec	10 LB
ECE	E11-106R-003389

Load capacity (lbs)

mph / psi	75
30	3520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 08:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..