

GR 288 - Specifiche tecniche



Description

GR 288 (G-2/L-2) è uno pneumatico versatile a carcassa diagonale per livellatrici o loader. Lo pneumatico è ideale per l'utilizzo nel settore costruzioni, preparazione del sito, costruzioni stradali nonché altri ambienti morbidi o fangosi. Il disegno del battistrada ha ottime proprietà di autopulitura che si traducono in eccellente trazione. Grazie alla speciale mescola resistente a tagli e strappi, lo pneumatico assicura un lungo ciclo di vita.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Dozer • Pala caricatrice

OTR: Motolivellatrice

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions US Standard

Usa code	94014446
Ply Rating	16
Overall Width (inch)	20.5
Overall Diameter (inch)	58.3
Static Loaded Radius (inch)	25.8
Rolling Circumference (inch)	173.1
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
ECE	E11-106R-005405
TRA Code	G2/L2
Tread Depth	36

Load capacity (lbs)

mph / psi	33	51
25	8800	-
5	-	18200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..