

GR 288 - Scheda tecnica



Description

GR 288 (G-2/L-2) è uno pneumatico versatile a carcassa diagonale per livellatrici o loader. Lo pneumatico è ideale per l'utilizzo nel settore costruzioni, preparazione del sito, costruzioni stradali nonché altri ambienti morbidi o fangosi. Il disegno del battistrada ha ottime proprietà di autopulitura che si traducono in eccellente trazione. Grazie alla speciale miscela resistente a tagli e strappi, lo pneumatico assicura un lungo ciclo di vita.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Dozer • Pala caricatrice

OTR: Motolivellatrice

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	ECE
15.5 - 25	STANDARD	94014415	G2/L2	12	12.00/1.3	12.00/1.3 (DC)	15.2	50	22.5	148.5	TL	30	E11-106R-003606
17.5 - 25	DUAL BEAD HD	94028313	G2/L2	20	14.00/1.5	14.00/1.3 (DC)	17.5	52.4	23.5	155.5	TT	32	E11-106R-005407
17.5 - 25	STANDARD	94014422	G2/L2	12	14.00/1.5	14.00/1.5 (DC) ; 14.00/1.3 (DC)	17.5	52.4	23.5	155.5	TL	32	E11-106R-005339
17.5 - 25	STANDARD	94014439	G2/L2	16	14.00/1.5	14.00/1.3 (DC)	17.5	52.4	23.5	155.5	TL	32	E11-106R-004561
20.5 - 25	STANDARD	94014446	G2/L2	16	17.00/2.0	17.00/1.7	20.5	58.3	25.8	173.1	TL	36	E11-106R-005405
20.5 - 25	STANDARD	94035632	G2/L2	20	17.00/2.0	17.00/1.7	20.5	58.3	25.8	173.1	TL	36	E11-106R-005180
23.5 - 25	STANDARD	94014453	G2/L2	16	19.50/2.5		23.4	63.4	27.9	188.3	TL	38	E11-106R-005406
23.5 - 25	STANDARD	94014460	G2/L2	20	19.50/2.5		23.4	63.4	27.9	188.3	TL	38	E11-106R-005181

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 18:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..