

I - 1 - Specifiche tecniche



Description

I-1 è stato progettato per il trasporto su campo e su strada nonché per le operazioni per la lavorazione del terreno con attrezzi agricoli e rimorchi. I-1 è uno pneumatico ad alta velocità che ottimizza i tempi di trasferimento, così che potrete concentrarvi sulla vostra attività principale. Il disegno speciale del battistrada assicura un ciclo di vita lungo dello pneumatico anche in condizioni dure e con la presenza di stoppie nel campo.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	9.5L - 15 SL
LI/SS	121 D

Dimensions International Standard

Ply Rating	12
Section Width (mm)	241
Overall Diameter (mm)	765
Static Loaded Radius (mm)	340
Rolling Circumference (mm)	2242
Rim Rec	7.00
Rim Alt	8 LB
ECE	E11-106R-003383
TRA Code	I1

Load capacity (Kg)

km/h / bar	4.40
65	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 04:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..