

LG 408 - Specifiche tecniche



Description

LG 408 è un pneumatico per tappeti erbosi e il giardinaggio, idoneo per tosaerba e piccoli trattori. Lo specifico disegno del battistrada, rende lo pneumatico delicato sul terreno prevenendo danni al terreno erboso. LG 408 è disponibile in una versione "aramid belted", con cinture in aramide, per utilizzatori che richiedono una maggiore resistenza alla perforazione.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Tosaerba • Trattorino

Version	STANDARD
Type	TL
Tyre Size	24 X 13.00 - 12

Dimensions US Standard

Usa code	94012862
Ply Rating	4
Section Width (inch)	12.8
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.6
Rolling Circumference (inch)	69.1
Rim Rec	10.5 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005204

Load capacity (lbs)

mph / psi	20
10	1840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..