

LG RIB PLUS - Specifiche tecniche



Description

LG RIB PLUS è uno pneumatico per prati e giardini adatto per l'utilizzo su tosaerba, piccoli trattori e spandivoltafieno. Il disegno del battistrada è stato appositamente progettato per fare in modo che lo pneumatico sia più delicato sul terreno, evitando di danneggiare il manto erboso agevolando al contempo la manipolazione. Il profilo arrotondato permette all'LG RIB PLUS di scorrere facilmente sul campo pur mantenendo la giusta aderenza.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Tosaerba • Trattorino

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions US Standard

Usa code	94065530
Ply Rating	10
Section Width (inch)	6.7
Overall Diameter (inch)	16.1
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90

Load capacity (lbs)

mph / psi	72
10	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..