

LG RIB - Specifiche tecniche



Description

LG RIB è uno pneumatico per tappeti erbosi e il giardinaggio, idoneo per tosaerba e piccoli trattori. Il disegno del battistrada è stato realizzato per rendere lo pneumatico delicato sul terreno prevenendo danni al terreno erboso facilitando nel contempo la manipolazione e le manovre. LG RIB è disponibile in una versione "aramid belted", con cinture in aramide, per utilizzatori che richiedono una maggiore resistenza alla perforazione.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Tosaerba • Trattorino

Version	ARAMID BELTED
Type	TL
Tyre Size	15 X 6.00 - 6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	152
Overall Diameter (mm)	365
Static Loaded Radius (mm)	159
Rolling Circumference (mm)	1059
Rim Rec	4.50 A
ECE	E11-106R-003504

Load capacity (Kg)

km/h / bar	3.20
15	335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 00:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..