

LIFTMAX LM 63 - Scheda tecnica



Description

LIFTMAX LM 63 è stato particolarmente sviluppato per le operazioni industriali e di logistica. Il disegno del battistrada a 3-costole offre una bassa resistenza al rotolamento, una buona tenuta sul bagnato e un'usura uniforme del battistrada, insieme a una migliore maneggevolezza. Questo pneumatico radiale All Steel con cinture in acciaio multistrato assicura minori vibrazioni abbinate a una maggiore stabilità e comfort.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Mietitrebbia

Industriale: Tow Tractor • Rimorchio

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type	ECE
180/70 R 8 (18X7 R 8)	STANDARD	94067008	125 A5	4.33R		6.7	18.1	TL	
180/70 R 8 IMP (18X7 R 8)	STANDARD	94067602	120 A8	4.33R		6.7	18.1	TL	E11-106R-006845
6.00 R 9	STANDARD	94063901	121 A5	4.00E		6.3	21.3	TL	
6.50 R 10	STANDARD	94066247	128 A5	5.00F	5.50 F	6.9	23.3	TL	
7.00 R 12	STANDARD	94066209	136 A5	5.00S		7.7	26.6	TL	
7.00 R 15	STANDARD	94066834	143 A5	5.50	5.00	7.8	29.1	TL	
8.25 R 15	STANDARD	94063635	153 A5	6.5	7.0	9.4	33.2	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 15:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..