

## LOADER SPECIAL - Specifiche tecniche



### Description

LOADER SPECIAL (L-5) è uno pneumatico a struttura diagonale che tiene i vostri loader in moto assicurando un'eccellente efficienza nelle operazioni pesanti con rocce. L'ottima trazione e l'eccezionale resistenza ai tagli daranno una spinta alla vostra produttività.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Dozer • Pala caricatrice

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

## Dimensions US Standard

Usa code	94034734
Ply Rating	28
Overall Width (inch)	30.3
Overall Diameter (inch)	76
Static Loaded Radius (inch)	34.8
Rolling Circumference (inch)	226.5
Rim Rec	25.00/3.5
TRA Code	L5
Tread Depth	125

## Load capacity (lbs)

mph / psi	62
5	38600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 10:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..