

## LOADER SPECIAL - Specifiche tecniche



### Description

LOADER SPECIAL (L-5) è uno pneumatico a struttura diagonale che tiene i vostri loader in moto assicurando un'eccellente efficienza nelle operazioni pesanti con rocce. L'ottima trazione e l'eccezionale resistenza ai tagli daranno una spinta alla vostra produttività.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Dozer • Pala caricatrice

Version	STEEL BELTED
Type	TL
Tyre Size	45/65 - 45

## Dimensions US Standard

Usa code	94056903
Ply Rating	58
Overall Width (inch)	46.7
Overall Diameter (inch)	109.6
Rim Rec	36.00/4.5
TRA Code	L5
Tread Depth	146

## Load capacity (lbs)

mph / psi	98
5	110000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 10:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..