

MAGLIFT ECO - Scheda tecnica



Description

MAGLIFT ECO è stato particolarmente sviluppato per applicazioni con carrelli elevatori. Lo pneumatico si distingue per il suo disegno con ramponi larghi che garantisce massima stabilità e distribuzione ottimizzata dei carichi. La sua struttura rinforzata elimina il rischio di slittamento, mentre il particolare bordo di protezione del cerchio protegge lo pneumatico contro danni. MAGLIFT ECO mostra eccellente trazione nonché bassa resistenza al rotolamento e ottima resistenza al calore, assicurando un'eccellente efficienza.

UM

US Standard

Construction

◆ SOLID

Machinery

Industriale: Carrello elevatore

SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	Type	TMPH
15 X 4.5 - 8 (125 / 75 - 8)	LIP	94065417	3.00 D - 8		4.3	14.9		0
15 X 4.5 - 8 (125 / 75 - 8)	STANDARD	94065400	3.00 D - 8		4.3	14.9		0
16 X 6 - 8 (150 / 75 - 8)	LIP	94064748	4.33 R - 8		5.5	16		0
16 X 6 - 8 (150 / 75 - 8)	STANDARD	94064731	4.33 R - 8		5.5	16		0
18 X 7 - 8 (180/70 - 8)	LIP	94060450	4.33 R - 8		5.2	17.8		0
18 X 7 - 8 (180/70 - 8)	STANDARD	94060627	4.33 R - 8		5.2	17.8		0
4.00 - 8	LIP	94065875	3.00 D - 8		3.9	15.9		0
4.00 - 8	STANDARD	94065868	3.00 D - 8		3.9	15.9		0
5.00 - 8	LIP	94060443	3.00 D - 8		4.4	17.9		0
5.00 - 8	STANDARD	94061969	3.00 D - 8		4.4	17.9		0
21 X 8 - 9 (200 / 75 - 9)	LIP	94065639	6.00 E - 9		6.9	20.5		0
21 X 8 - 9 (200 / 75 - 9)	STANDARD	94065622	6.00 E - 9		6.9	20.5		0
6.00 - 9	LIP	94057955	4.00 E - 9		5.1	20.6		1
6.00 - 9	STANDARD	94058310	4.00 E - 9		5.1	20.6		1
200/50 - 10	LIP	94065561	6.50 F - 10		7.1	17.8		0
200/50 - 10	STANDARD	94065554	6.50 F - 10		7.1	17.8		0
23 X 9 - 10 (225 / 75 - 10)	LIP	94065431	6.50 F - 10		7.2	22.8		0
23 X 9 - 10 (225 / 75 - 10)	STANDARD	94065424	6.50 F - 10		7.2	22.8		0
6.50 - 10	LIP	94058303	5.00 F - 10		6	22.5		1
6.50 - 10	STANDARD	94058020	5.00 F - 10		6	22.5		1
27 X 10 - 12 (250 / 75 - 12)	LIP	94066094	8.00 G - 12		8.9	26.4		0
27 X 10 - 12 (250 / 75 - 12)	STANDARD	94066100	8.00 G - 12		8.9	26.4		0
7.00 - 12	LIP	94057948	5.00 S - 12		6.5	25.4		0
7.00 - 12	STANDARD	94057825	5.00 S - 12		6.5	25.4		0
250 - 15 (250 / 70 - 15)	LIP	94065455	7.0 - 15		8.2	28.1		0
250 - 15 (250 / 70 - 15)	STANDARD	94065448	7.0 - 15		8.2	28.1		0
300 - 15 (315/70-15)	LIP	94064076	8.0-15		9.5	32.3		0
300 - 15 (315/70-15)	STANDARD	94063918	8.0-15		9.5	32.3		0
8.15-15/28x9-15 (225/75-15)	LIP	94063376	7.0 - 15		8	27.2		0
8.15-15/28x9-15 (225/75-15)	STANDARD	94062843	7.0 - 15		8	27.2		0
8.25 - 15	LIP	94064069	6.5 - 15		8.3	31.8		0
8.25 - 15	STANDARD	94063703	6.5 - 15		8.3	31.8		0

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and

pressure condition.

Printed on 29/04/2025 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..