

MAGLIFT PREMIUM - Scheda tecnica



Description

MAGLIFT PREMIUM è uno pneumatico solido particolarmente sviluppato per operazioni pesanti con carrelli elevatori in applicazioni portuali, minerarie o cantieri di demolizione. Il battistrada extra profondo (25% in più rispetto alla versione standard) con il suo disegno aggressivo e robusto offre eccezionale trazione anteriore e laterale oltre ad un controllo eccellente della sterzata. La speciale mescola del battistrada si traduce in straordinaria resistenza a tagli e lacerazioni e prolunga la vita dello pneumatico. Ulteriori vantaggi sono la bassa resistenza al rotolamento e una corsa regolare.

UM

International Standard

Construction

◆ SOLID

Machinery

Industriale: Carrello elevatore

SIZE	Version	RIM REC	RIM ALT	SW	OD	Type
6.00 - 9	LIP	4.00 E - 9		137	536	
6.00 - 9	LIP - NON MARKING	4.00 E - 9		137	536	
6.00 - 9	STANDARD	4.00 E - 9		137	536	
6.00 - 9	STANDARD - NON MARKING	4.00 E - 9		137	536	
6.50 - 10	LIP	5.00 F - 10		150	582	
6.50 - 10	STANDARD	5.00 F - 10		150	582	
7.00 - 12	LIP	5.00 S - 12		163	664	
7.00 - 12	STANDARD	5.00 S - 12		163	664	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 11:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..