

MINE STAR XL - Scheda tecnica



Description

MINE STAR XL è uno pneumatico convenzionale particolarmente adatto alle pale per trasporto materiale (LHD) nelle operazioni sotterranee di carico e trasporto. Il disegno largo del battistrada con tasselli aperti evita che sassi o altri residui rocciosi rimangano incastrati nello pneumatico garantendo peraltro una trazione eccezionale. L'impronta più ampia rende MINE STAR XL il miglior alleato per le operazioni pesanti nelle mine sotterranee. MINE STAR XL è realizzato con una speciale mescola del battistrada che conferisce una straordinaria resistenza a tagli e lacerazioni, assicurando maggiore efficienza operativa, un ciclo di vita dello pneumatico più lungo nonché tempi di fermo macchina ridotti.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Pala LHD

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	Type	Tread Depth
55 X 20.00 - 34	STANDARD	94075911	L5	44	16.00		19.1	53.7	TL	77

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..