

MP 590 - Specifiche tecniche



Description

MP 590 è uno pneumatico agro-industriale per operazioni di carico con sollevatori telescopici e carrelli elevatori. Lo pneumatico offre ottima trazione e stabilità eccellente insieme a durabilità superiore.

UM

US Standard

Construction

• BIAS

Machinery

Agricoltura: Sollevatore telescopico

Industriale: Carrello elevatore • Sollevatore telescopico •

Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

Dimensions US Standard

Usa code	94044191
Ply Rating	20
Section Width (inch)	18.9
Overall Diameter (inch)	46.9
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	139.1
Rim Rec	14.0
ECE	E11-106R-004408

Load capacity (lbs)

mph / psi	109
25 DW	12790
20 DW	14330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 04:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..