

MT 617 - Specifiche tecniche



Description

MT 617 è stato specificamente sviluppato per autocarri militari. È uno pneumatico run flat che offre ottima trazione insieme ad elevata resistenza alle forature. Inoltre, la protezione del fianco contribuisce a un ciclo di vita prolungato dello pneumatico.

UM

US Standard

Construction

✚ BIAS

Machinery

Industriale: Autocarro militare

Version	ARAMID BELTED
Type	TL
Tyre Size	14.5 - 21

Dimensions US Standard

Usa code	94030880
Ply Rating	12
Section Width (inch)	15.4
Overall Diameter (inch)	48
Rim Rec	10

Load capacity (lbs)

mph / psi	70	61
55 LS	7950	-
55 LD	-	6970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..