



MULTI RIB - Specifiche tecniche



Description

MULTI RIB è uno pneumatico agro-industriale per la lavorazione del terreno e applicazioni di trasporto con trattori 2WD/2RM e attrezzi agricoli. Lo pneumatico offre eccezionale manovrabilità durante l'intero ciclo di vita del prodotto. Esistono svariate versioni per soddisfare ogni esigenza: una versione "aramid-belted" con cinture in aramide per una maggiore resistenza alla perforazione, mentre la versione "HD" è realizzata con una speciale mescola resistente a tagli e lacerazioni.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricoltura: Trattore 2WD • Attrezzi agricoli

Version	ARAMID BELTED HD
Type	TL
Tyre Size	11.00 - 16

Dimensions International Standard

Ply Rating	12
Section Width (mm)	315
Overall Diameter (mm)	930
Rim Rec	W10 L
Rim Alt	W 8 ; W 8 L
ECE	E11-106R-005377

Load capacity (Kg)

km/h / bar	4.10
40	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..