

MULTIMAX MP 513 - Specifiche tecniche



Description

MULTIMAX MP 513 è stato progettato da BKT per applicazioni con veicoli polivalenti nel settore municipalità/manutenzione e trasporto, sia per uso agricolo che industriale. Lo pneumatico è ideale per veicoli universali ed i camion di fertilizzante. Grazie alla carcassa robusta in nylon rinforzata con cinture in acciaio, MULTIMAX MP 513 consente il trasporto di carichi pesanti ad alte velocità, fornendo un'esperienza di guida confortevole. Garantisce inoltre una maggiore durabilità e trazione nonché eccezionali proprietà di autopulitura.

UM

International Standard

Construction



RADIAL

Machinery

Agricoltura: Veicolo universale • Autocarro per fertilizzanti
Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	495/70 R 24 MPT
LI/SS	155 G

Dimensions International Standard

Section Width (mm)	499
Overall Diameter (mm)	1304
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3974
Rim Rec	W 16 L
Rim Alt	DW 15 L ; DW 16 L ; W 15 L
ECE	E4-54R-0029057

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1980	2340	2840	3250	3875
65	2150	2540	3085	3530	4205
40	2280	2695	3270	3740	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..