

MULTIMAX MP 522 - Specifiche tecniche



Description

MULTIMAX MP 522 è lo pneumatico polivalente di BKT sviluppato per campi di applicazione nel settore agro-industriale. È adatto per tutte le operazioni di sollevamento e di carico su veicoli quali sollevatori telescopici e pale compatte. Stabilità e trazione sono i punti di forza abbinati all'eccezionale resistenza alle forature. Grazie alla speciale mescola, MULTIMAX MP 522 ha un'incredibile resistenza a tagli e lacerazioni.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Pala compatta • Sollevatore telescopico
Industriale: Pala compatta • Sollevatore telescopico

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 480/80 R 26 IND |
| LI/SS | 167 A8/B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94073108 |
| Section Width (inch) | 18.9 |
| Overall Diameter (inch) | 56.2 |
| Static Loaded Radius (inch) | 25.1 |
| Rolling Circumference (inch) | 168.8 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 16 L |
| ECE | E11-106R-008146 |

Load capacity (lbs)

| mph / psi | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 46 | 49 | 52 | 55 | 58 | 61 | 64 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5680 | 6210 | 6730 | 7260 | 7800 | 8330 | 8860 | 9390 | 9920 | 10450 | 10970 | 11500 | 12010 | - | - |
| 25 | 5680 | 6210 | 6730 | 7260 | 7800 | 8330 | 8860 | 9390 | 9920 | 10450 | 10970 | 11500 | 12010 | - | - |
| 20 | 6150 | 6710 | 7270 | 7830 | 8390 | 8950 | 9510 | 10060 | 10630 | 11190 | 11750 | 12300 | 12860 | - | - |
| 15 | 6370 | 6960 | 7540 | 8110 | 8700 | 9280 | 9870 | 10440 | 11020 | 11610 | 12180 | 12760 | 13340 | - | - |
| 5 Cvc. | 7050 | 7840 | 8620 | 9400 | 10180 | 10970 | 11750 | 12530 | 13320 | 14100 | 14880 | 16450 | 18020 | - | - |
| Static | 10800 | 12000 | 13200 | 14410 | 15610 | 16810 | 18010 | 19210 | 20410 | 21620 | 22820 | 24020 | 25230 | 26430 | 27630 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..