

PL 846 - Specifiche tecniche



Description

PL 846 è stato particolarmente progettato per attrezzi agricoli nelle applicazioni per la lavorazione della terra. Lo pneumatico offre straordinaria stabilità ed eccezionale trazione insieme ad un'elevata resistenza ad ogni tipo di taglio. PL 846 è lo pneumatico ideale su superfici rocciose.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions International Standard

Ply Rating	10
Section Width (mm)	160
Overall Diameter (mm)	540
Rim Rec	4.00 E

Load capacity (Kg)

km/h / bar	8.50
25	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 06:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..