

PORTMAX PM 90 - Specifiche tecniche



Description

PORTMAX PM 90 è stato particolarmente progettato per reach stacker impiegati in svariate applicazioni inclusi la movimentazione industriale e operazioni nelle acciaierie. La speciale miscela del battistrada assicura particolare resistenza al calore nonché un ciclo di vita prolungato dello pneumatico. PORTMAX PM 90 offre una resistenza ridotta al rotolamento che migliora il risparmio di carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 33
LI/SS	214 A5

Dimensions International Standard

Overall Width (mm)	485
Overall Diameter (mm)	1845
Static Loaded Radius (mm)	857
Rolling Circumference (mm)	5624
Rim Rec	13.00/2.50
Rim Alt	13.00/2.50 IF
Star Rating	***

Load capacity (Kg)

km/h / bar	10.00
25	21200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 09:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..